

Document Name		Dial back & Dial security setup	
Document Type		How To	
Product or Technology related		Courier modems	
Document Number	EMEA CSO 0001	Document Date	02/07/01

Dial back & Dial security setup

For security reasons, it is sometimes necessary to verify the identity of the person who is calling, which is the function performed by the Dial Security option. If you want the modem to identify and then dial back automatically the caller (or another number) you should use the Dial Back function.

Generally, this type of procedure is used to secure access to a machine used as a server. In order to use this function the computer must be equipped with a Courier (or Courier I) modem. This modem is called the host modem in the following procedure.

On the host modem, and only on the host modem, you must configure what are known as accounts. In the following example, the password chosen is "explosif", you can obviously replace this with your own password (a maximum of 8 characters). In order to do this, in Hyperterminal you must type: (attention, these commands will erase all existing accounts).

```
AT%E=1%E=2%E=3%E=4%E=5
AT%A0=EXPLOSIF,Y,N,N,
AT%L=PW0
ATS53.0=1.1=1.2=1&W
ATS0=5&W
AT&W
ATZ!
```

Remember to configure the client modem to reply automatically (S0=5&W) if you are using Hyperterminal. N.B. The recall delay is 1 minute.

For more information, please visit us at <http://www.usr-emea.com/>.